



## APPLICATIONS

**Eni Rotra MP 75W-90** is a special synthetic technology lubricant for manual gearboxes requiring an API GL-4 or GL-5 level of performance. It has been especially formulated for the lubrication of both gearboxes and differentials in modern vehicles.

## CUSTOMER ADVANTAGES

- **Eni Rotra MP 75W-90** guarantees an extraordinary thermo-oxidative stability, an exceptional protection against corrosion, and full seal compatibility. It can satisfy the most demanding specifications of OEMs for Long-drain operations.

## SPECIFICATIONS - APPROVALS

- API GL-4 + GL-5
- API MT-1
- SAE J2360
- MAN 341 type Z2
- MAN 342 type M3
- Scania STO 1 : 0
- ZF TE-ML 02B, 05A, 12L, 12N (Approved)
- ZF TE-ML 16B, 17B, 19C, 21A (Approved)





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	875
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	16.3
Viscosity Index	ASTM D 2270	-	155
Viscosity at -40°C	ASTM D 2983	mPa·s	135000
Pour point	ASTM D 5950	°C	-42



eni