

Eni i-Sint pro light 5W-40



Eco friendly

APPLICATIONS

Eni i-Sint pro light 5W-40 is an innovative fully synthetic lubricant with 'mid SAPS' characteristics designed to meet the lubrication needs of the recent technology engines powered by gasoline, diesel or gas/LPG. The product contributes to reducing polluting exhaust emissions in accordance with the increasingly stringent environmental impact standards. In addition, it is designed to meet the severe requirements of premium German brands.

CUSTOMER ADVANTAGES

- The viscosimetric features of its formulation facilitate cold starts and make it possible to save fuel which results in a reduction of CO2 emissions at the exhaust.
- **Eni i-Sint pro light 5W-40** resists deterioration, especially related to thermo-oxidative phenomena for long-term exposure to high temperatures in the presence of air and other agents.
- Metal based additives present in engine oils, if used at certain concentrations, can compromise the operation and efficiency of exhaust emission reduction systems, resulting in increased emissions. **Eni i-Sint pro light 5W-40** contains a limited level of these additives and thus ensures better efficiency and durability of these devices.

SPECIFICATIONS

- API SN/CF
- ACEA C3
- MB 229.31
- MB 229.51
- Porsche A40



Eni i-Sint pro light 5W-40



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/dm ³	0.851
Viscosity at 100°C	ASTM D 445	mm ² /s	13.8
Viscosity at 40°C	ASTM D 445	mm ² /s	82
Viscosity Index	ASTM D 2270	-	175
Viscosity at -30°C	ASTM D 5293	cP	5075
Flash point COC	ASTM D 92	°C	225
Pour point	ASTM D 97	°C	-42
B. N.	ASTM D 2896	mg KOH/g	7.4



eni