



APPLICATIONS

Eco friendly

Fuel economy

Eni i-Sint Protection 0W-20 is a fully synthetic lubricant designed and developed to meet the lubrication requirements of engines fitted in newly-manufactured cars, including hybrids that operate according to the maintenance procedures prescribed by the manufacturers.

CUSTOMER ADVANTAGES

- The presence in the formulation of low volatility components and simultaneously high thermal stability dramatically reduces oil consumption.
- The high-flow properties ensure better engine lubrication effectively reducing friction and significantly contributing to fuel savings with consequent reduced carbon dioxide (CO2) emissions.
- **Eni i-Sint Protection 0W-20** ensures, thanks to its extreme fluidity, excellent cold start, ensuring the best lubrication even at very low temperatures and at the same time maintaining a particularly durable oil film even at high operating temperatures. **Eni i-Sint Protection 0W-20** is suitable for cars equipped with Start & Stop systems.
- The special formulation of the product ensures maximum protection reducing the wear effects also in the most extreme driving conditions, always ensuring that the engine maintains its original performance.

SPECIFICATIONS

- API SP RC
- ILSAC GF-6A





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	B&C
Density at 15°C	ASTM D 4052	kg/dm ³	0.845
Viscosity at 100°C	ASTM D 445	mm ² /s	8.6
Viscosity at 40°C	ASTM D 445	mm ² /s	43.4
Viscosity Index	ASTM D 2270	-	180
Viscosity at -35°C	ASTM D 5293	mPa·s	4440
Flash point COC	ASTM D 92	°C	232
Pour point	ASTM D 6749	°C	-45

