



# Eni i-Sint pro light 5W-30

**Eni i-Sint pro light 5W-30** is an innovative fully synthetic lubricant with "Mid SAPS" (MS) characteristics, specifically formulated for gasoline or diesel engines of the latest models of passenger cars and light vans.

## PROPERTIES AND PERFORMANCE

- Its 'mid SAPS' (MS) characteristics ensure efficiency and durability of after-treatment devices.
- It allows easier engine startup and give high fuel economy benefits, with consequent reduction of CO<sub>2</sub> emissions.
- Its high quality formulation has been developed to meet the severe requirements of many European OEMs. In particular, it strongly resists to high temperatures oxidation in presence of air and other agents, allowing longer drain intervals.

## CHARACTERISTICS

Property	Method	Unit	Typical Value
Density at 15°C	ASTM D4052	kg/dm <sup>3</sup>	0.851
Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.2
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	72
Viscosity Index	ASTM D2270	-	169
Viscosity at -30°C	ASTM D5293	cP	5375
Flash point COC	ASTM D92	°C	230
Pour point	ASTM D97	°C	-42
B.N.	ASTM D2896	Mg KOH/g	7.4

## SPECIFICATIONS

**Eni i-Sint pro light 5W-30** meets or exceeds the requirements of:

- ACEA C3-21
- API SP/SP RC/SN PLUS
- ILSAC GF-6
- MB 229.31
- MB 229.51
- MB 229.52
- Opel OV0401547
- RN0710/0700
- BMW Longlife-04